

Chimney



Now with
**more
Power**
700 m³/hr

Adore the beauty. Experience the power.



Glen presents a range of chimneys that are truly rare combinations of beauty and power. Their smart, elegant, aerodynamic looks are bound to sway you off your feet. The strong, powerful motors deliver a powerful suction of upto 750m³/hr. The next generation choke free baffle filters ensure maximum convenience. Now grime, greasiness and fumes in the kitchen are a thing of the past.

Bi-rotational technology
Suction power upto 700m³/hr



The new exclusive Bi-rotational technology from Glen guarantees the maximum Suction power for Indian oily cooking.

At the heart of this technology are two high performance motors rotating in opposite direction. This rotation creates a special low pressure zone, which forces the fumes to rush in, resulting in a much higher airflow as compared to the conventional systems. This inward pull also prevents the fumes from escaping from the sides of the chimney.

Next Generation Baffle Filter



The next generation choke free Baffle Filter for Indian oily cooking, with thoughtful features to ensure the very best in performance, convenience and safety.



Dynamic Airflow
The advanced design ensures that it does not reduce the airflow and accumulates the oily deposits without choking the filter. Moreover it's very easy to clean.



Better Hinge Support & Dual Lock
This Filter hinges on two deep hinge points and is securely locked in place with a dual locking system.



Easy to Operate Lock
The international convenient way to operate the filter

Thermal Overload Protector for motor protection



In view of continually fluctuating voltages and the erratic power supplies, this smart chimney is provided with another intelligent feature. The TOP switches off the supply if the motor gets too much heated up and prevents motor burnouts.

Push Button Controls

New soft touch push button controls for convenient operation. Also available with slider controls (SL models)

Flame Retardant

The housing, plastic parts and even the wires of the chimney are made up of flame retardant, low smoke material. This enhances safety.

Carbon Filter

Optional carbon filters are available for installation where ducting is not possible and the chimney needs to be installed in re-circulation mode. In this case the suction capacity drops by about 30%. Therefore it is highly recommended to install the chimney in exhaust mode.



GL 6001 PBBF



GL 6014 PBBF



GL 6013 SLBF



GL 6002 SLBF

Specifications *

Model	Size (cms)	Motors	Fans	Wattage Motor	Wattage Total	Airflow (m ³ /hr)	Static Pressure (Pa)	Speeds	Control	Metal Filter	Carbon Filter
GL 6001	60/70	2	2	145	370	700	375	3	PB	BF	<input type="checkbox"/>
GL 6002	60	1	2	145/155	225	750/1000	375/430	3	SL/PB	BF	<input type="checkbox"/>
GL 6013	60/90	2	2	145	370	700	375	3	SL	BF	<input type="checkbox"/>
GL 6014	60/90	2	2	145	370	700	375	3	PB	BF	<input type="checkbox"/>

Optional SL Slider Control PB Push Button Control
CF Cassette Filter BF Baffle Filter

* Subject to change without prior notice.

Colour/Glen0615/20K



Glen Appliances Pvt. Ltd.
I-34, DLF Industrial Area, Phase-I, Faridabad
T: 0129-225 4191-3 E: info@glenindia.com
W: www.glenindia.com

